

Contents

Abstract	i
Zusammenfassung	iii
Acknowledgements	v
List of Symbols	vii
List of Abbreviations	ix
List of Figures	xv
List of Tables	xix
1 Introduction	1
2 State of the Art	3
2.1 The Family of Micro and Nano Resonators	3
2.1.1 3D Bulk Resonators	3
2.1.2 2D Resonators	6
2.1.3 1D Beam Resonators	8
2.2 Tuning Mechanisms of Doubly Clamped 1D Resonators . . .	9
2.2.1 Gate Bias Tuning	9
2.2.2 Axial Strain Tuning	12
2.2.3 Overview of Achieved Tuning Ranges	15
2.3 Current Research Objectives and Challenges	17
2.3.1 Modelling of the CNT as Continuum	17
2.3.2 Quality Factor	20
2.3.3 CNT Contacts to Electrodes	22
2.4 Thesis Motivation and Outline	24
3 Mechanics of Doubly Clamped Resonators	27
3.1 Flexural Vibrations in Beams	27
3.2 Boundary Conditions	32
3.3 Modelling the Dynamics of CNT Resonators	36
3.3.1 Effective Stiffness of a Clamped-Clamped Beam under Tension	38
3.3.2 Effective Excitation Force	39
3.3.3 The Explicit Duffing Equation for CNT Resonators . .	43

3.4	Harmonic Balancing for the Duffing Equation	44
3.5	CNTs as Continuum Model	46
3.6	Modelling Results for a Typical CNT	49
4	The Mechanical Straining Platform	55
4.1	Design of the MEMS Straining Platform	56
4.1.1	The Thermal Actuators	58
4.1.2	Electrode Design	60
4.2	Fabrication of the MEMS Straining Platform	62
4.2.1	L0: Wafer Preparation and Marker Deposition	65
4.2.2	L1: Silicon Nitride Removal	66
4.2.3	L2: Gate Patterning	66
4.2.4	L3: Electrode Deposition	67
4.2.5	L4: Beam-Shape and Actuator Patterning	68
4.2.6	L5: Mesa Etch	69
4.2.7	L6: Backside Etch and Release	69
4.2.8	Device Assembly and Wirebonding	71
4.2.9	CNT Dry-Transfer	72
4.3	Characterization of the Thermal Actuators	74
4.3.1	Experimental Setup	74
4.3.2	Displacement Extraction of SEM Images	74
4.4	COMSOL FEM Simulation of the MEMS Straining Platform	80
4.4.1	COMSOL Model	80
4.4.2	Simulation Results and Analysis	84
4.5	Results of the Actuator Characterization	87
5	Electrical Conduction in CNT Resonators	89
5.1	Transfer Characteristics of CNT FETs	90
5.2	Experimental Setup	92
5.3	Frequency Down-Mixing	93
5.3.1	Conductive Current	95
5.3.2	Piezoresistive Current	97
5.4	Lorentzian Peak Shapes and Fitting Procedure	99
5.5	Electrical Measurement Results	100
5.5.1	Background Current Analysis	104
5.5.2	Current Modelling of CNTs with Harmonic Balancing	104
6	Results	109
6.1	Pure Axial Strain Tuning	110
6.2	Influence of the Strain on the Transfer Curve	117
6.2.1	Influence of the Mass-loading Factor	118
6.3	Combination of Axial Strain and Gate Bias Tuning	121
7	Conclusions and Outlook	127
7.1	Summary and Conclusions	127

7.2	Outlook	129
A	Mechanical Model: Supplementary Material	131
A.1	Galerkin's Method for the Motional PDE	131
A.2	Beam Elongation due to Transverse Displacement	134
A.3	Harmonic Balancing Equations	135
A.3.1	First Order HB Ansatz	136
A.3.2	Second Order HB Ansatz	137
B	Current Model: Supplementary Material	139
B.1	Conductive Current Component at the Lock-in Amplifier	139
B.1.1	1ω Readout-Technique	139
B.1.2	2ω Readout-Technique	140
B.2	Piezo Current Component at the Lock-in Amplifier	141
B.2.1	1ω Readout-Technique	141
B.2.2	2ω Readout-Technique	142
C	Detailed Fabrication Procedure	145
C.1	L1: SiN Etch-Through	145
C.2	L2: Gate Patterning	145
C.3	L3: Electrode Deposition	146
C.4	L4: Beam Shape Patterning	146
C.5	L5: Mesa Etch	147
C.6	L6: Backside Etch and Release	147
C.7	Marker Design	148
C.8	Datasheet: Wafer	149
D	Device Directory	151
D.1	Devices without Axial Straining Capability	151
D.2	SJDS 123	151
D.3	Devices with Axial Straining Capability	155
D.4	Slacked CNT on MV 01	157
D.5	HB Fitting Results on Device MV39	157
E	Actuator Directory	159
E.1	L2	159
E.2	MV 20	159
E.3	L5	160
E.4	L6	160
E.5	MV 12	161
E.6	MV 21	161
E.7	L3	162
E.8	L7	162
E.9	MV 01	163
F	COMSOL Simulation: Supplementary Material	165

Contents

Bibliography	167
Publications	183
Curriculum Vitae	185